





Tap-offs with F-connections, frequency range up to 2400 MHz

Type	AFC 1011 S	AFC 1511 S	AFC 2011 S	AFC 2511 S
Order No.	947 564-002	947 565-002	947 658-002	947 659-002



Throughpass attenuation				
Frequency range MHz 5-40	2 dB	1.5 dB	1.5 dB	1.5 dB
Frequency range MHz 40-1000	2.5 dB	1.5 dB	1.5 dB	1.5 dB
Frequency range GHz 1-2.4	3.2 dB	2.2 dB	2.2 dB	2.2 dB
Tap-off attenuation				
Frequency range MHz 5-40	11 dB	15 dB	20 dB	25 dB
Frequency range MHz 40-1000	10 dB	15 dB	20 dB	25 dB
Frequency range GHz 1-2.4	10 dB	15 dB	20 dB	25 dB
Directional attenuation				
Frequency range MHz 5-40	26 dB	30 dB	35 dB	40 dB
Frequency range MHz 40-1000	22 dB	25 dB	30 dB	30 dB
Frequency range GHz 1-2.4	20 -18 dB	22 -20 dB	25 dB	28 -25 dB
Technical data				
Dimensions Ø	53x53x16 mm	53x53x16 mm	53x53x16 mm	53x53x16 mm
Drawing				

- Die-cast housing
- Two splitters can be mounted on top of each other using the spacer supplied
- For 1 SAT-IF distribution in buildings
- Remote feed via master, max. 1 A/24 V DC
- Conforms to EN 50083-2

